

# Antenna, Mercedes-Benz Type

**P/N: 921638401**

## DRP-7 Kit

Replaces the OEM Mercedes-Benz parts listed below:

### *Installation Instructions*

124 820 57 75

124 820 57 75 80

124 820 57 75 88

#### **Installing Your Antenna** (for Mercedes-Benz models 124, 129, 140):

1. Disconnect the battery.
2. Remove the old antenna and installation hardware from the vehicle.
3. Snap the 4-pole connector (from the DIN-ISO adapter harness) onto the new antenna mast tube.
4. Remove the signal splitter and its mounting hardware from the old antenna and transfer it to the new one.
5. Connect the Blue wire (included with the new antenna) to the signal splitter.
6. Install the new antenna in the same manner as the original. The small bracket(s) supplied with the antenna are inserted into the bottom of the antenna motor housing, as needed.
7. Connect the vehicle harness connector to the adapter connector on the mast tube.

(Note: If your vehicle is equipped with a Mercedes-Benz cellular phone, you must do the following):

- a) Cut off the round bushing (2.5mm) from the blue (0.75 MM<sup>2</sup>) cellular phone prewired harness antenna control wire.
  - b) Solder or crimp the flat ISO connector (supplied with the new antenna).
  - c) Remove the locking strap; insert the wire with the terminal into location #2 of the DIN-ISO adapter harness.
  - d) Re-install the locking strap onto the side of the connector.
8. Connect the 4-pole ISO connector to the antenna motor.
  9. Reconnect the battery.
  10. Test the radio and antenna functions.

#### **Need more help?**

For product information, white papers, technical presentations, FAQ's and more, please visit our website:

<http://www.hirschmann-car.com>

For technical support or customer service, call us direct at (248) 373-7150

**Hirschmann Car Communication**

1116 Centre Road  
Auburn Hills, MI 48326 USA  
T: 248-373-7150 F: 248-276-2350