


*Grundträger Alustyle*  
*Alustyle Basic carrier bars*  
*Support de base Alustyle*  
*Soportes básicos Alustyle*  
*Supporto di base Alustyle*  
*Allesdrager Alustyle*



### Mounting instructions

#### Alustyle Basic carrier bars C 124

1. Open all flaps on decorative strips on roof of vehicle (Fig. 1).



2. Clip open covering flap, 1, on basic rack with key (Fig. 2).



3. Unlock lock knobs, 2, and pull out as far as possible - flap, 50, will then open slightly. Open flap, 50, completely (Fig. 3).



**Note!** The supporting feet of the basic carrier bar are marked vr (front right), hr (rear right) (Fig. 4).



4. Position rack on roof of vehicle; recesses are provided on supporting foot for decorative strip flaps.


5. Tighten bolts, 3, lightly by hand (Fig. 5).



6. Fit contact shoes, 51, to decorative strip (Fig. 6).




7. Tighten bolts, 3, firmly with screwdriver (Fig. 7).



8. Close flap, 50, to first engaging position.

9. Press in lock knobs, 2, completely and lock (Fig. 8).



10. Remove key and close covering cap, 1.

### Specification

Weight: 3 kg

Permissible roof load: 100 kg

### Instructions for use

Items of luggage must not project excessively beyond the load surface. The load must be evenly distributed, with the centre of gravity as low as possible. Each item of luggage must be secured to both rack elements with a rope or rubber belt. Elastic tensioners must not be used with the basic luggage rack.

Before every journey and during long trips, the rack should be checked for tight fit; if necessary, tighten the tensioning bolts.

The vehicle's handling will be altered due to the raised centre of gravity and the larger surface area exposed to the wind. Be sure to adapt your driving style to these conditions. For reasons of general road safety, the rack should be removed from the vehicle when not in use.

Two keys are provided with each lockable roof accessory. Attached to one key is an adhesive label with the key number. Please affix this label to your personal vehicle data card. If both keys are lost, you can only obtain replacement keys from your Mercedes-Benz customer service centre by quoting this number.