



INTERNET ARCHIVE  
WayBack Machine

http://www.amsoil.com/StoreFront/atf.aspx

78 captures  
1 Oct 05 - 5 Dec 10

Go

DEC 5 FEB FEB  
2008 2009 2010

Close  
Help



**APPLICATIONS**

AMSOIL Synthetic Universal Automatic Transmission Fluid is completely compatible with other synthetic and petroleum automatic transmission fluids. AMSOIL ATF is a universal, multi-functional fluid that greatly reduces the need for specialized fluid inventories and the possibilities of misapplication.

AMSOIL ATF is recommended for transmission, hydraulic and other applications requiring any of the following specifications:

- GM DEXRON® II, III & VI
- Ford MERCON®, MERCON® V & SP
- Chrysler ATF+ through ATF+4®
- Honda Z-1 (**Not for use in CVT transmissions**)
- Toyota Type T and T-IV
- Mitsubishi/Hyundai Diamond SP II & III
- Allison C-3, C-4
- Caterpillar TO-2
- Voith G607, G1363
- ZF TE-ML 14A, 14B, 14C
- Mercedes Benz 236.1, 236.2, 236.6, 236.7, 236.9
- BMW 7045E
- NAG 1 & 2
- JWS 3309
- LT 71141 (ESSO)
- Nissan Matic D, J & K
- Vickers I-286S & M-2950S

Excellent for power steering units that use ATF.

Not for use in CVT transmissions.

**SERVICE LIFE**


AMSOIL Synthetic Automatic Transmission Fluid is recommended for use up to 50,000 miles under severe service\* and up to 100,000 miles under normal service\* or according to the vehicle manufacturer recommended intervals, whichever is longer. AMSOIL recommends thoroughly draining the transmission and flushing with new AMSOIL ATF to achieve a minimum 90% purity of new transmission fluid. Drain intervals may be extended further with oil analysis.

\* As defined by the vehicle or transmission manufacturer.

**HEALTH & SAFETY**

This product is not expected to cause health concerns when used for the intended application and according to the recommendations in the Material Safety Data Sheet (MSDS). MSDS's are available upon request at 715-392-7101 or [on our website](#). **Keep Out of Reach of Children.** Don't pollute. Return used oil to collection centers.

<b>TYPICAL TECHNICAL PROPERTIES</b> Revised as of 7/07	
<b>AMSOIL Synthetic Universal Automatic Transmission Fluid (ATF)</b>	
Kinematic Viscosity @ 100°C, cSt (ASTM D-445)	6.8
Kinematic Viscosity @ 40°C, cSt (ASTM D-445)	32.4



78 captures  
1 Oct 05 - 5 Dec 10

http://www.amsoil.com/StoreFront/atf.aspx  
viscosity index (ASTM D-2270)











Go

DEC FEB FEB  
5 172  
2008 2009 2010

Close Help

Noack Volatility, % weight loss (ASTM D-5800)	11.0
Flash Point °C (°F) (ASTM D-92)	220 (428)
Pour Point °C (°F) (ASTM D-97)	-53 (-63)
Four Ball Wear Test, Scar in mm; 40 kg, 75°C, 1200 rpm, 1 hr (ASTM D-4172B)	0.44
Brookfield Viscosity (cP)	-20°C = 1245
Brookfield Viscosity (cP)	-40°C = 9087

**AMSOIL ALSO OFFERS**

Order Fax Line: (715)392-5225 ISO 9001:2000 Certified Product Technical Ser

[AMSOIL Warranty](#) | [AMSOIL Racing](#) | [Media Relations](#) | [Clothing & Promotional Items](#) | [FAQs](#) | [AMSOIL Privacy Policy](#) | [Satisfied Customers](#) | [Site Map](#) | [Oil Analyzi](#)  
 Copyright 1996-2009 AMSOIL INC. All rights reserved.