



# ATF 236.14

## Automatic Transmission Fluid for Mercedes Passenger Car Automatic Transmission

**100% Synthetic**

### TYPE OF USE

High performance 100% synthetic lubricant specially engineered for Mercedes RWD (Rear Wheel Drive) and 4x4 AWD (All Wheel Drive) passenger cars, SUV's and light duty utility vehicles automatic transmissions where MB-Approval 236.14 specification is required.

Especially recommended for use in all Mercedes vehicles fitted with the 7 speed RWD automatic transmissions (NAG2) and all AMG models, as well as Mercedes 5 speed automatic transmissions with regulated torque converter lockup clutch, where MB-Approval 236.14 specification is required.

Before use always refer to the owner manual of the vehicle.

### PERFORMANCES

APPROVALS: **MB-Approval 236.14**

MOTUL ATF 236.14 is a 100% Synthetic high technology lubricant featuring outstanding performance with regards to conventional DEXRON and MERCON standards requirements.

MOTUL ATF 236.14 exclusive and dedicated formula:

- Protects the numerous, compact and heavily loaded gears thanks to advance anti-wear properties.
- Extends life time duration, high shear stability at hot temperature and oxidation resistance.
- Allows fuel economy for cars fitted with automatic gearboxes by reducing epicyclical gears friction.
- Improves automatic gearboxes reaction at cold temperature.
- Provides anti-shudder performance and then avoids vibrations on engine fly wheel.
- Gives superior automatic transmission response: smooth shift feel and minimizing shift time lag.
- Anti-wear, anti-corrosion, anti-foam.

### RECOMMENDATIONS

Can be mixed with similar lubricants.

Oil change: according to manufacturer's recommendations and adapt according to your own use.

Before use always refer to the owner manual of the vehicle.

### PROPERTIES

Color	Visual	Red
Density at 20°C (68°F)	ASTM1298	0.850
Viscosity at 40°C (104°F)	ASTM D445	29.6 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D445	6.6 mm <sup>2</sup> /s
Viscosity Index	ASTM D2270	192
Pour Point	ASTM D97	-54°C / -65.2°F
Flash Point	ASTM D92	210°C / 410°F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel : 33 1 48 11 70 00 - Fax : 33 1 48 33 28 79 - Web Site: [www.motul.com](http://www.motul.com)