



Product Information

A PRODUCT OF VALVOLINE

Import Multi-Vehicle ATF

Valvoline Import Multi-Vehicle ATF (Automatic Transmission Fluid) is specifically formulated for use in most Toyota, Nissan, Honda and other imported vehicles. It is formulated with all synthetic base stocks and sophisticated additive system to ensure optimal transmission performance in wide variety of vehicles. Valvoline Import Multi-Vehicle ATF can also be used in many domestic vehicles. It meets requirements of General Motors and Ford vehicles

The Valvoline Import Multi-Vehicle ATF Advantages:

- Full synthetic fluid
- Reduces varnish and sludge formation
- Protects against wear
- Improves and maintains smooth shifting over long service intervals
- Provides excellent flow properties at low temperatures and greater film protection at high temperatures

Performance Levels

Recommended for use in GM, Ford, Toyota, Honda, Nissan, Hyundai and other imported vehicles
Suitable for use in:

Ford MERCON® and MERCON®V applications
GM DEXRON®-II and DEXRON®-III applications
BMW LT 71141, ETL-7045E and M-1375.4 applications
Nissan/Infiniti Nissan ATF, Matic D, Matic K and Matic J applications
Mitsubishi Diamond SP-II and SP-III applications
Subaru ATF-HP
Hyundai/ KIA SP-II, SP-III and SP-IV applications
Toyota/Lexus Type T, T-III and T-IV applications
Honda/Acura ATF-Z1 (except in CVTs) applications
Mercedes Benz NAG1 applications
Volvo passenger car applications
Volkswagen/Audi TL52162

Test	Typical Property
Viscosity @ 100°C, cSt	7.24
Viscosity @ 40°C, cSt	34.91
Viscosity Index	178
Calcium, mass %	.026
Phosphorus, mass %	0.065
Specific Gravity @ 60°F	0.851
Pour Point, °C,	-51
Brookfield Viscosity @ -40°C, cP	9680
Appearance	Red

Effective Date: 08/23/2012

Replaces: 06/11/2012

Alexey Stiop

Doc #-Rev 03