



> Search > Find an MSDS

## Mobil® 1 Truck & SUV

Most Advanced Performance Synthetic Engine Oil



Pdf



Print  
View



Product Description	Features & Benefits	Applications	Specifications & Approvals	Typical Properties	Health & Safety
------------------------	------------------------	--------------	-------------------------------	-----------------------	--------------------

### Product Description

Mobil 1 Truck & SUV is engineered for hard-working gasoline and diesel engines. Mobil 1 Truck & SUV is a high performance, fully synthetic engine oil that provides unsurpassed lubrication and extreme temperature performance for today's gasoline and diesel engines operating in severe applications.

### Features & Benefits

Mobil 1 Truck & SUV provides outstanding performance and protection for hardworking engines where towing, hauling and severe service are standard daily requirements.

- Exceptional high temperature protection for hot running engines under heavy load.
- Excellent low temperature protection for quick and easy start-ups in cold weather.
- Keeps engines clean through outstanding resistance to high temperature varnish and low temperature sludge deposit formation.
- Excellent oil consumption control
- Outstanding wear protection and performance reserve to maximize engine life
- Provides owners of both gasoline and diesel engines a single solution for exceptional performance and protection

### Applications

- Mobil 1 Truck & SUV is a 5W-40 viscosity grade product and is recommended by ExxonMobil where 5W-30, 10W-30 and 15W-40 lubricants are specified. Consult your owner's manual for specific manufacturer recommendations which may be required for warranty protection.
- Mobil 1 Truck and SUV is recommended for use in gasoline and diesel powered trucks and SUVs built by Ford, GM, and DaimlerChrysler.
- Mobil 1 Truck and SUV further meets the diesel engine requirements of Cummins, Powerstroke, Duramax and Navistar – for bigger, heavier duty truck applications, such as delivery vans and utility fleets.
- Mobil 1 Truck and SUV is fully compatible with conventional engine oils.

[^\\_ Back to Top](#)

### **Specifications & Approvals**

Mobil 1 Truck & SUV meets or exceeds the following industry specifications:

API gasoline engine standards	SL,SJ
API diesel engine standards	CI-4, CH-4, CG-4, CF-4, CF

### **Typical Properties**

Mobil 1 Truck & SUV

SAE Grade                    5W-40

Viscosity, ASTM D 445



cSt @ 40°C	102
cSt @ 100°C	14.8
Viscosity Index, ASTM D 2270	151
Sulfated Ash, wt%, ASTM D 874	1.35
Total Base #, mg KOH/g, ASTM D 2896	12
Pour Point, °C, ASTM D 97	-45
Flash Point, °C, ASTM D 92	226
Density @ 15°C kg/l, ASTM D 4052	0.854

[▲ Back to Top](#)

#### **Health & Safety**

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design and Mobil 1 with Supersyn are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

Exxon Mobil Corporation  
3225 Gallows Road  
Fairfax, VA 22037  
1-800-Mobil25 (662-4525)

Due to continual product research and development, the information contained herein is subject to change without notification.

Typical Properties may vary slightly. This product data sheet is based on global product data sheets for use with products purchased in the U.S.

© 2001 Exxon Mobil Corporation. All rights reserved.



[ExxonMobil Home](#) | [Help](#) | [Sitemap](#) | [Contact Us](#) | [Privacy & Legal](#)