

Years & models: 1992-1995 124.034 & 124.036, 1992-1995 W140, and 1993-1995 R129				ASR = 013-545-39-32		
<b>The following live data parameters are available from vehicles with engines with LH fuel injection:</b>						
012-545-62-32		124-545-45-32		015-545-61-32	015-545-13-32	011-545-97-32
<b>LH-SFI (Fuel Injection)</b>	<b>EA/CC/ISC (E-GAS)</b>	<b>DI (EZL / Digital Ignition)</b>	<b>DM (Diagnostic Module)</b>	<b>BM (Basic Module)</b>		
<i>Personality Key S-20</i>		<i>Personality Key S-21</i>		<i>Personality Key S-20</i>		
O2 Sensor Voltage (mV)	Engine Speed (RPM)	Engine Speed (RPM)	Engine Speed (RPM)	Engine Speed (RPM)	Circuit 30 F2 (ok)	
Self Adaptation CTP Idle - (kg/h)	LF Speed (MPH or KPH)	Engine Coolant Temp (°C or °F)	Absolute Intake Manifold Pressure	Circuit 30 F3 (ok)		
Self Adaptation Lower Partial Load	LR Speed (MPH or KPH)	Intake Air Temperature (°C or °F)	Intake Air Temperature (°C or °F)	Circuit 30 F4 (ok)		
Self Adaptation Upper Partial Load	Cruise Control Sw. S40 'D' (On/Off)	Barometric Pressure (mbar)	Engine Coolant Temp (°C or °F)	Circuit 30 LH1-SFI Unfused (ok)		
O2 Sensor (Lambda) Control (%)	Cruise Control Switch S40 'A' (On/Off)	Manifold Air Pressure Differential (mbar)	Vehicle Speed (MPH or KPH)	Kickdown Switch Voltage		
Battery Voltage (V)	Cruise Control Switch S40 'R' (On/Off)	Ignition Angle (°)		Circuit 15 Voltage		
Engine Speed (RPM)	Cruise Control Switch S40 'O' (On/Off)	Catalyst Selected		Engine Speed (RPM)		
Basic Injection Duration (ms)	C.C. Switch S40 Safety Contact (On/Off)	Reference Resistor		Vehicle Speed (MPH or KPH)		
Injection Duration Correction (ms)	Potentiometer M16 / 1R2 (V)	Transmission Overload Protection Switch		Module Box Blower M2/2 (on/off)		
Hot Wire Air Mass (kg/h)	Reference Potentiometer M16 / 1R1 (V)	Battery Voltage (V)		A/C Compressor Signal (on/off)		
Hot Wire Voltage (V)	CTP (Idle) Switch S29/3 (On/Off)	Knock Control Act.		Electromagnetic Clutch A9K1 (on/off)		
Barometric Pressure (mbar)	Idle Speed Safety Switch M16 / 1S2 (On/Off)	Knock Ignition Angle Cylinder 1		Idle Speed Increase (on/off)		
Engine Coolant Temp 1 (°C or °F)	Safety Contact Switch M16 / 1S1 (On/Off)	Knock Ignition Angle Cylinder 2				
Engine Coolant Temp 2 (°C or °F)	Safety Fuel Shut-Off (On/Off)	Knock Ignition Angle Cylinder 3				
After Start Enrichment (Y/N)	A/C Compressor (On/Off)	Knock Ignition Angle Cylinder 4				
Deceleration Shutoff (Y/N)	CTP (Idle) Increase (On/Off)	Knock Ignition Angle Cylinder 5				
Air Pump (On/Off)	Stop Lamp Switch N.O. Contact (On/Off)	Knock Ignition Angle Cylinder 6			<b>Basic Module Actuator Tests:</b>	
Camshaft timing (On/Off)	Stop Lamp Switch N.C. Contact (On/Off)	Knock Ignition Angle Cylinder 7			Module Box Blower Motor	
Intake Air Temperature (°C or °F)	Trans. Range Selector Switch (P,R,N,D,S,L)	Knock Ignition Angle Cylinder 8				
CTP (Idle) Recognition (On/Off)	CAN Transmission from EA/CC/ISC (ok)	Ignition Voltage Cylinder 1				
Throttle Valve Angle (°)	CAN Reception from ASR (ok)	Ignition Voltage Cylinder 2				
WOT (Full Load) Recognition (On/Off)	CAN Reception from LH-SFI (ok)	Ignition Voltage Cylinder 3				
EGR (On/Off)	CAN Reception from DI (ok)	Ignition Voltage Cylinder 4				
Fuel Pump (On/Off)		Ignition Voltage Cylinder 5			<b>LH Injection Actuator Tests:</b>	
Canister Purge Duty Cycle (%)		Ignition Voltage Cylinder 6			Secondday Air Injection	
Vehicle Speed (MPH or KPH)		Ignition Voltage Cylinder 7			EGR	
Cylinder Shut-Off 1 (Y/N)		Ignition Voltage Cylinder 8			Adjustable Camshaft Timing 1	
Cylinder Shut-Off 2 (Y/N)		Combustion Time Cylinder 1			Adjustable Camshaft Timing 2	
Cylinder Shut-Off 3 (Y/N)		Combustion Time Cylinder 2			Injector #1	
Cylinder Shut-Off 4 (Y/N)		Combustion Time Cylinder 3			Injector #2	
Cylinder Shut-Off 5 (Y/N)		Combustion Time Cylinder 4			Injector #3	
Cylinder Shut-Off 6 (Y/N)		Combustion Time Cylinder 5			Injector #4	
Cylinder Shut-Off 7 (Y/N)		Combustion Time Cylinder 6			Injector #5	
Cylinder Shut-Off 8 (Y/N)		Combustion Time Cylinder 7			Injector #6	
LH-SFI Reference Resistor		Combustion Time Cylinder 8			Injector #7	
Circuit 50 (On/Off)		CAN Transmission from DI (ok)			Injector #8	
Safety Fuel Shut-Off (On/Off)		CAN Reception from LH-SFI (ok)			Purging	
CAN Reception from DI (ok)		CAN Reception from ASR (ok)			Upshift Delay	
CAN Reception from EA/CC/ISC (ok)		CAN Reception from EA/CC/ISC (ok)			Burnoff Control	
CAN Transmission from LH-SFI (ok)						

<b>Years &amp; models:</b>		
1993-1995 124.028, .032, .052, .066, .092 with 2.8L or 3.2L engine (all have HFM-SFI injection)		
1994-1996 W202 with 2.8L engine and HFM-SFI injection		
1996 W210 with 3.2L engine and HFM-SFI injection		
<b>The following live data parameters are available from vehicles with M104.9xx inline 6-cylinder engines with HFM fuel injection:</b>		
<b>HFM-SFI (Fuel Injection)</b>	<b>DM (Diagnostic Module)</b>	<b>EA/CC/ISC (E-GAS)</b>
O2 Sensor 1 Voltage (mV)	Engine Speed (RPM)	No communication
O2 Sensor (Lambda) Control (%)	Absolute Intake Manifold Pressure	<i>Snap-On software error - requires custom wiring to communicate, scanner is looking at the wrong signal line from the adapter.</i>
Self Adaptation Factor Lower Partial Load	Intake Air Temperature (°C or °F)	<i>With the modified wiring it will work fine.</i>
Self Adaptation Factor Upper Partial Load	Engine Coolant Temp (°C or °F)	
Air Mass (kg/h)	Vehicle Speed (MPH or KPH)	
After Start Enrichment (On/Off)		
Engine Coolant Temp (°C or °F)		
Air Pump (On/Off)		
Engine Speed (RPM)		
Nominal Engine Speed (RPM)		
Intake Manifold Switchover Valve (on/off)		
Throttle Valve Angle (°)		
CTP (Idle) Contact (On/Off)		
WOT (Full Load) Contact (On/Off)		
Deceleration Shutoff (On/Off)		
Intake Air Temperature (°C or °F)		<b>HFM Actuator Tests:</b>
Injection Duration (ms)		Camshaft
Camshaft Solenoid (On/Off)		EGR
Self-Adaptation Idle Speed Air (kg/h)		Air Pump
Ignition Angle (°)		Injector Cylinder #1
AC Compressor (On/Off)		Injector Cylinder #2
Reference Resistor		Injector Cylinder #3
Starter Signal Circuit 50 (On/Off)		Injector Cylinder #4
Selector Lever Position (P, R, N, D, S, L)		Injector Cylinder #5
Vehicle Speed (MPH or KPH)		Injector Cylinder #6
Warm-Up		Purging