



P30.10-0231-09

A	Model 124	14	Accelerator pedal lever	30/6	Rubber grommet
B	Models 129, 140	30	Control cable	35	Return spring
		9	Control lever	37	Holder
		10	Fixed lever		Arrow Control cable mount

☒☒	Removal, installation		
1	Remove guide (30/5)	First pull plastic nipple out of guide, do not damage i Installation: Ensure that plastic nipple catches in guide	
2	Unhook control cable (30) from control lever (9)		
3	Press plastic clip (30/4) together and remove from fixed lever (10) together with control cable		
4	Remove footwell paneling		
5	Unhook control cable mount (arrow) from accelerator pedal lever (14)	Model 124 Unhook return spring (35), hook in Models 129, 140 Remove holder (37), install	
6	Push control cable (30) toward exterior from passenger compartment	i Do not press out rubber grommet (30/6)	
7	Completely remove control cable (30) from engine compartment		
8	Reinstall in opposite order		
9	Lubricate control cable (30) between guide (30/5) and end element with corrosion protection grease		*BR00.45-Z-1006-06A
10	Check control, adjust	With ASR, code 471a Without ASR, code 471a	AR30.10-P-1010EA AR30.10-P-1010EB

Repair materials

Number	Designation	Order number
BR00.45-Z-1006-06A	Anti-corrosion grease 40 g / DB supply specification 6834.00	A 001 989 37 51 10